



SAE 30, 40 Engine Oils

Medallion Plus® SAE 30, 40 Engine Oils contain a special blend of additives that keep engines clean of harmful carbon deposits, varnishes and resins. Medallion Plus SAE 30, 40 Engine Oils also protect engines from sludge, rust and acid build-up. These oils perform efficiently in gasoline engines and are outstanding for stop-and-go taxi fleets, city delivery vehicles and public utility fleets.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>SAE 30</u>	<u>SAE 40</u>
Viscosity @ 40°C, cSt	D445	104.0	137.40
Viscosity @ 100°C, cSt	D445	11.90	14.40
Viscosity Index	D2270	101	103
Flash Point, COC, °C	D92	232	238
Flash Point, COC, °F	D92	450	460
Pour Point, °C	D97	-24	-18
Pour Point, °F	D97	-11	0
Color	D1500	2.5	2.5
Gravity, °API	D287	30.0	30.0
Sulfated Ash, %	D874	.98	.98
Phos., %	D4951	0.077	0.077
Zinc, %	D4951	0.085	0.085
Total Base No. (TBN)	D2896	7.4	7.4

Meets or exceeds the following tests and requirements:

- API Service Classification - SM
- Daimler Chrysler MS-6395-J, MS-9742, MS-9754, MS-9767
- Ford Motor Company - WSS-M2C153-G; WSS-M2C153-H
- General Motors - 9986187
- Military Specifications - CID-AA-52039

NOTE: Certain tests apply to specific SAE grades.