



## Full Synthetic GL-5 Gear Oils

Medallion Plus® Full Synthetic GL-5 Gear Oils are formulated with synthetic base stocks for use in universal duty hypoid or spiral bevel gear differentials and manual transmissions in cars, light trucks and SUV's. It provides optimum axle and transmission protection and thermally stable extreme pressure agents protect against shock loading and wear.

Medallion Plus Full Synthetic GL-5 Gear Oils are fortified with anti-oxidants and corrosion inhibitors to resist damage from rust and oxidation.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>SAE 75W-90</u>	<u>SAE 75W-140</u>
Viscosity @ 40°C, cSt	D-445	100.00	194.00
Viscosity @ 100°C, cSt	D-445	14.50	25.00
Viscosity Index	D-2270	160	160
Brookfield Viscosity @ 40°C, cP	D-2983	115,000	125,000
Flash Point, COC, °C (°F)	D-92	180 (356)	180
Pour Point, °C (°F)	D-97	-36 (-33)	-36
Color	D-1500	2.0	2.0
Gravity, °API	D-287	30.5	30.5
Copper Strip Corrosion (250°F)	D-130	1a	1a

Meets or exceeds the following tests and requirements:  
API Service Classification – GL-5  
Limited Slip Performance