



Full Synthetic Engine Oils

Medallion Plus® Full Synthetic Engine Oils are blended with the highest quality synthesized base stocks and contain a special blend of additives that keep engines clean of harmful carbon deposits, varnishes and resins.

Medallion Plus Full Synthetic Engine Oils also protect engines from sludge, rust and acid build-up. These oils perform efficiently in gasoline engines and are outstanding for stop-and-go taxi fleets, city delivery vehicles and public utility fleets.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>SAE 0W-16</u>	<u>SAE 0W-20</u>	<u>SAE 5W-20</u>	<u>SAE 5W-30</u>	<u>SAE 10W-30</u>
Viscosity @ -35°C, cP	D-5293	5600	6000	N/A	N/A	N/A
Viscosity @ -30°C, cP	D-5293	N/A	N/A	4600	5800	N/A
Viscosity @ -25°C, cP	D-5293	N/A	N/A	N/A	N/A	5800
Viscosity @ 40°C, cSt	D-445	37.30	45.00	44.00	58.00	63.00
Viscosity @ 100°C, cSt	D-445	7.20	8.50	8.30	10.50	10.80
Viscosity Index	D-2270	160	170	160	170	170
Flash Point, COC, °C	D-92	210	213	213	213	213
Flash Point, COC, °F	D-92	410	415	415	415	415
Pour Point, °C	D-97	-45	-40	-40	-40	-40
Pour Point, °F	D-97	-49	-40	-40	-40	-40
Color	D-1500	2.0	2.0	2.0	2.0	2.0
Gravity, °API	D-287	36.5	36.0	35.5	36.0	36.0

Meets or exceeds the following tests and requirements:

- API Service Classification - SN, ILSAC GF-5
- Chrysler MS-11999, MS-12007, MS-12015, MS-6395-S
- Resource Conserving
- Ford Motor Company - WSS-M2C945A, WSS-M2C946A
- Honda/Toyota Genuine Oils

NOTE: Certain tests apply to specific SAE grades.