



Full Synthetic dexos1[®] Engine Oils

Medallion Plus[®] Full Synthetic dexos1[®] Engine Oils are blended with the highest quality synthesized base stocks and contain a special blend of additives that keep engines clean of harmful carbon deposits, varnishes and resins. With recent additive improvements, these more robust offerings are equipped to negate the destructive effects of Low Speed Pre-Ignition and provide improved Turbocharger protection by reducing turbo coking and deposits.

Medallion Plus Full Synthetic dexos1[®] Engine Oils also protect engines from sludge, rust and acid build-up. These oils perform efficiently in gasoline engines and are outstanding for stop-and-go taxi fleets, city delivery vehicles and public utility fleets.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>SAE 0W-20</u>	<u>SAE 5W-30</u>
Viscosity @ -35°C, cP	D-5293	6000	N/A
Viscosity @ -30°C, cP	D-5293	N/A	5800
Viscosity @ -25°C, cP	D-5293	N/A	N/A
Viscosity @ 40°C, cSt	D-445	45.00	58.00
Viscosity @ 100°C, cSt	D-445	8.50	10.50
Viscosity Index	D-2270	170	170
Flash Point, COC, °C	D-92	213	213
Flash Point, COC, °F	D-92	415	415
Pour Point, °C	D-97	-40	-40
Pour Point, °F	D-97	-40	-40
Color	D-1500	2.0	2.0
Gravity, °API	D-287	36.0	36.0

Meets or exceeds the following tests and requirements:

API Service Classification – SP, SN PLUS, SN, ILSAC GF-6A

Chrysler MS-11999, MS-12007, MS-12015, MS-6395-S

Resource Conserving

Ford Motor Company - WSS-M2C945-A, WSS-M2C946-A

General Motors – dexos1 – License Numbers D325BACJ148, D32502CJ148 (0W-20)

License Numbers D325AACJ148, D32503CJ148 (5W-30)

Honda/Toyota Genuine Oils

NOTE: Certain tests apply to specific SAE grades.