



Full Synthetic Global Multi-Vehicle ATF

Medallion Plus® Full Synthetic Global Multi-Vehicle Automatic Transmission Fluid (ATF) represents the latest technology in full synthetic automatic transmission fluids. It is specifically formulated for the newest generation of high efficiency transmissions and is also a fuel-efficient choice for older models as well.

This ATF allows for inventory optimization as it meets multiple applications and provides excellent service in a wide variety of automatic transmission applications. It provides improved oxidation and thermal stability in a fully synthetic formula. It possesses outstanding low temperature performance, superior anti-wear protection and improved torque transfer.

Medallion Plus® Full Synthetic Global Multi-Vehicle ATF may be used in a wide variety of applications including most General Motors, Ford, Chrysler, Toyota/Lexus, Nissan/Infiniti, and Honda/Acura transmissions, as well as transmissions installed in Hyundai, Isuzu, Jaguar, Kia, Land Rover, Mazda, Mercedes, Mitsubishi, Porsche, BMW, MINI, SAAB, Subaru, Volvo, and VW/Audi cars and light trucks. Check the owner's manual for specific recommendations.

PROPERTIES & SPECIFICATIONS:

PROPERTY	ASTM TEST METHOD	TEST SPECIFICATIONS
VISCOSITY @ 40°C, CST	D-445	31.00
VISCOSITY @ 100°C, CST	D-445	6.10
VISCOSITY INDEX	D-2270	150
FLASH POINT, COC, °C (°F)	D-92	208 (406)
POUR POINT, °C (°F)	D-97	-48 (-54)
COLOR	D-1500	Red
GRAVITY, °API	D-4052	32.9

Not for use in transmissions requiring Ford Type F, Continuously Variable Transmission (CVT) applications, or Double Clutch Transmissions (DCT).

Always consult your owner's manual for your specific recommended automatic transmission fluid. ATF Viscosity may preclude Global ATF coverage.

If you have questions, please contact PetroChoice Technical Services, techservices@petrochoice.com, for assistance with determining the correct ATF coverage for your applications.



Full Synthetic Global Multi-Vehicle ATF

SPECIFICATIONS & APPROVALS

THIS PRODUCT MEETS OR EXCEEDS THE REQUIREMENTS OF:

ATF	TYPE A, SUFFIX A, 134, 3353, L12108, M115, M-1375.4, M-1375.6
AISIN WARNER	JWS 3324, AW-1, ATF-0WS
ALLISON	C3, C4
BMW	ATF 3+, ATF6, M-L12108, P/N 83 22 0 142 516, P/N 83 22 0 3997 114, P/N 83 22 2 152 426, P/N 83 22 2 163 514,
CATERPILLAR	POWER SHIFT TO-2
FORD	MERCON LV, MERCON SP
GM	AW-1, DEXRON II, DEXRON IIE, DEXRON III, DEXRON IIIG, DEXRON IIIH, DEXRON VI, DEXRON T-IV, P/N 1940773, WS P/N 88863400 P/N 88863401
HONDA/ACURA	ATF 3.0, ATF 3.1, DW-1 (NOT CVTS)
HYUNDAI	SP-IV, SP-IVM, SPH-IV, SP-IV-RR, TIV, WS NWS 9638T-5, P/N 040000C90SG
INFINITI	MATIC-R, MATIC-S, MATIC-W
ISUZU	ATF II, ATF III, GENUINE ATF, ATF WSI, SCS
JAGUAR	02JDE 26444, FLUID 8432
JAMA	JASO M3154, CLASS 1-A-LV
LAND ROVER	AW-1 P/N LR0022460, P/N TYK500050, LR023288/023289
MASERATI	OIL NO. 231603
MAZDA	FZ, TYPE T-IV
MERCEDES BENZ	236.12, 236.14, 236.41
MINI	DIAQUEEN ATF-MA1, DIAQUEEN ATF-PA, ATF-J3, SP-IV
NISSAN	MATIC-R, MATIC-S, MATIC-W
PORSCHE	P/N 000 043 304 00/01, P/N 000 043 305 43, P/N 000 043 305 54, P/N 000 043 306 24, P/N 958 300 901 00
SAAB	P/N 93 165 147
STELLANTIS	AS68RC, 8&9 SPEED, P/N 68218925AA/AB, AW-1, P/N 68092912AA, DEX-VI, P/N 68043742AA, FIAT 9.55550-AV2, FIAT 9.55550-AV5, FIAT 9.55550-AV6, P/N 05127382, P/N 68157995AA/AB, SP-IV, P/N 68171866AA, SP-IV, P/N 68171869AA
SUBARU	ATF WS
SUZUKI	MATIC-S
TOYOTA	ATF-FZ, JWS 3324, ATF WS, NWS9638
VOLVO	P/N 31 256 774, P/N 31 256 775
VW	G 052 533, G 055 005 A2, G 055 162 A2, G 055 162 A6, G 055 540 A2, G 060 162 A2
ZF	LIFEGUARDFLUID 6 (ZF S671 090 255), LIFEGUARDFLUID 8 (ZF S671 090 312), LIFEGUARDFLUID 9 (ZF AA01 500 001)

TO-14/08.16.2023